

# SAFETY DATA SHEET BARTOLINE WHITE SPIRIT

According to Regulation (EC) No 1907/2006 Annex II as amended by Regulation (EU) 2015/830.

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name BARTOLINE WHITE SPIRIT

Internal identification 19920000

REACH registration number 01-2119458049-33-XXXX

**REACH registration notes**The EC substance definition and related classification & labelling has been developed in the

framework of the Regulation (EC) No 1907/2006 (REACH). For information about the related

CAS number see section 16 of this MSDS.

**EC number** 919-446-0

1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** General degreasing solvent. Paint brush cleaner Paint thinner.

Uses advised against Not to be used for cleaning skin as this may lead to skin disorders.

1.3. Details of the supplier of the safety data sheet

Supplier Bartoline Limited

Barmston Close Beverley East Yorkshire HU17 0LW 01482 678710 info@bartoline.co.uk

Contact person HSE MANAGER

1.4. Emergency telephone number

Emergency telephone 01482 678727 (0800-1700 Monday to Friday)

National emergency telephone National Poisons Information Service (24hours) 0844 892 0111

number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Flam. Liq. 3 - H226

Health hazards STOT SE 3 - H336 STOT RE 1 - H372 Asp. Tox. 1 - H304 STOT SE 3 - H336

**Environmental hazards** Aquatic Chronic 2 - H411

**Human health** Prolonged skin contact may cause redness and irritation. Ingestion of even small quantities

may be fatal. Vapours and spray/mists in high concentrations are narcotic. Prolonged contact

causes serious eye and tissue damage.

# **BARTOLINE WHITE SPIRIT**

**Environmental** The product contains a substance which is toxic to aquatic organisms and which may cause

long-term adverse effects in the aquatic environment.

Physicochemical Vapours may form explosive mixtures with air. Vapours may be ignited by a spark, a hot

surface or an ember. Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers. Containers can burst violently or explode when

heated, due to excessive pressure build-up.

#### 2.2. Label elements

**EC number** 919-446-0

#### **Pictogram**









Signal word

Danger

Hazard statements H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements** P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe vapour/spray.

P271 Use only outdoors or in a well-ventilated area.

Wear rubber/PVC protective gloves and chemical safety glasses.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF SWALLOWED: Immediately call a doctor/NHS 111.

P331 Do NOT induce vomiting.

Call a doctor/NHS 111 if you feel unwell.

IF ON SKIN: Wash with plenty of soap and water.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Dispose of contents/container to hazardous waste collection point.

Supplemental label

information

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) 100 %

# 2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

# **BARTOLINE WHITE SPIRIT**

#### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics,

100.0%

aromatics (2-25%) 100 %

CAS number: — EC number: 919-446-0

REACH registration number: 01-

2119458049-33-XXXX

Classification

Flam. Liq. 3 - H226 STOT SE 3 - H336 STOT RE 1 - H372 Asp. Tox. 1 - H304 STOT SE 3 - H336 Aquatic Chronic 2 - H411

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Product name BARTOLINE WHITE SPIRIT

REACH registration number 01-2119458049-33-XXXX

framework of the Regulation (EC) No 1907/2006 (REACH). For information about the related

CAS number see section 16 of this MSDS.

**EC number** 919-446-0

Composition comments A complex and variable combination of paraffinic, cyclic and aromatic hydrocarbons having a

carbon number range predominantly of C9 to C12 and boiling in the range of approximately

135°C to 220°C.

The aromatic content is between 2% and 25%.

# SECTION 4: First aid measures

# 4.1. Description of first aid measures

General information Remove affected person from source of contamination. IN CASE OF SERIOUS OR

PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

**Inhalation** Move the exposed person to fresh air at once. Get medical attention. Provide rest, warmth

and fresh air. When breathing is difficult, properly trained personnel may assist affected

person by administering oxygen.

Ingestion DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR

DRINK FLUIDS! If vomiting occurs, keep head low so that stomach content doesn't get into

the lungs. Get medical attention immediately! Provide rest, warmth and fresh air.

**Skin contact** Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical

attention promptly if symptoms occur after washing.

Eye contact Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do.

Continue rinsing. Get medical attention if symptoms are severe or persist after washing.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue. It may

be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it from the affected person, or

wear gloves.

# 4.2. Most important symptoms and effects, both acute and delayed

# **BARTOLINE WHITE SPIRIT**

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

**Inhalation** Vapours inhaled in strong concentration have a narcotic effect on the central nervous system.

Irritation of the respiratory tract due to excessive fume, causes headache, drowsiness or other

effects to the central nervous system, loss of consciousness.

Ingestion If swallowed accidentally, the product may enter the lungs due to its low viscosity and lead to

the rapid development of very serious pulmonary lesions (medical survey during 48 hours).

Nausea, Vomiting, Abdominal pain.

**Skin contact** Prolonged or repeated contact may cause irritation and dry skin.

**Eye contact** Burning feeling and temporary redness.

# 4.3. Indication of any immediate medical attention and special treatment needed

Specific treatments The most severe risk is through ingestion, the product may enter the lungs due to its low

viscosity and lead to the rapid development of very serious inhalation pulmonary lesions

(medical survey during 48 hours).

# SECTION 5: Firefighting measures

# 5.1. Extinguishing media

**Suitable extinguishing media** Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

# 5.2. Special hazards arising from the substance or mixture

Specific hazards Vapours are heavier than air and may spread near ground and travel a considerable distance

to a source of ignition and flash back.

Hazardous combustion

products

Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly

dangerous if inhaled in confined spaces or at high concentrations.

# 5.3. Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

Containers close to fire should be removed or cooled with water.

Special protective equipment for firefighters

In case of a large fire or in confined or poorly ventilated spaces, wear full fire resistant protective clothing and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# SECTION 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate area. Keep unnecessary and unprotected personnel away from the spillage. No

smoking, sparks, flames or other sources of ignition near spillage. Do not touch or walk into spilled material. Do not enter storage areas or confined spaces unless adequately ventilated. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Take precautionary measures against static discharges.

Take care as floors and other surfaces may become slippery.

#### **BARTOLINE WHITE SPIRIT**

For non-emergency personnel Land Spill: Eliminate all ignition sources (no smoking, flares, sparks or flames in the immediate area). Stop leak if you can do so without risk. Do not touch or walk through spilled material. Prevent entry into waterways, sewers, basements or confined areas. A vapoursuppressing foam may be used to reduce vapour. Dam or absorb spillage with noncombustible material such as earth, sand or booms, pads or absorbent granules. Use clean non-sparking tools to collect absorbed material. Water Spill:

> Stop leak if you can do so without risk. Eliminate sources of ignition. Warn or evacuate occupants in surrounding and downwind areas if required, due to the toxicity or flammability of the material. If the flashpoint exceeds the ambient air temperature by 10 degrees C or more, use containment booms and remove from the surface by skimming or with suitable absorbents. If the flashpoint does not exceed the ambient air temperature by at least 10 degrees C, use booms as a barrier to protect shorelines and allow material to evaporate. Seek the advice of a specialist before using dispersants.

#### For emergency responders

Wear protective clothing as described in Section 8 of this safety data sheet. See section 11 for additional information on health hazards. For waste disposal, see section 13.

#### 6.2. Environmental precautions

# **Environmental precautions**

The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment. The product is insoluble in water and will spread on the water surface. Do not discharge into drains, water courses or onto the ground. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

#### 6.3. Methods and material for containment and cleaning up

# Methods for cleaning up

Stop leak if safe to do so. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. To prevent release, place container with damaged side up. Cover large spillages with alcohol-resistant foam. Absorb spillage with non-combustible, absorbent material. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor.

# 6.4. Reference to other sections

#### Reference to other sections

For personal protection, see Section 8. For waste disposal, see Section 13. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards.

# SECTION 7: Handling and storage

# 7.1. Precautions for safe handling

# Usage precautions

Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Use explosion proof electric equipment. Storage tanks and other containers must be grounded. Wear full protective clothing for prolonged exposure and/or high concentrations. Contaminated clothing and shoes must be discarded. Contaminated rags and cloths must be put in fireproof containers for disposal. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Avoid spilling and release to the environment such as drains and watercourses.

# Advice on general occupational hygiene

Persons with impaired lung function should not handle this product.. Do not eat, drink or smoke when using this product. Provide shower facilities near the workplace. Wash promptly with soap and water if skin becomes contaminated. Take off immediately all contaminated clothing and wash it before reuse. Promptly remove any clothing that becomes wet or contaminated. Remove contaminated clothing and protective equipment before entering eating areas. Wash at the end of each work shift and before eating, smoking and using the toilet. Use appropriate hand lotion to prevent defatting and cracking of skin.

# **BARTOLINE WHITE SPIRIT**

# 7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep

container tightly sealed when not in use. Keep locked up and out of the reach of children. Store in a demarcated bunded area to prevent release to drains and/or watercourses. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with oxidising agents. Keep away from food, drink and animal feeding stuffs. Use containers made of the following materials: Carbon steel. Glass. Mild steel. Stainless

steel. High-density polyethylene (HDPE) Polyethylene terephthalate (PET)

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2. FOR FURTHER IN

FORMATION REFER TO EXPOSURE SCENARIOS.

Usage description In General:

Keep containers closed when not in use.

Keep containers upright.

Use only in well ventilated areas, ideally outdoors.

Open containers slowly in order to release any pressure build up that may occur.

Keep out of reach of children.

Apply "common sense" measures when using this product.

When using transfer required amount to a suitable container such as glass, metal PET or

HDPE.

Avoid all contact with skin and eyes.

#### SECTION 8: Exposure Controls/personal protection

# 8.1. Control parameters

#### Occupational exposure limits

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) 100 %

Long-term exposure limit (8-hour TWA): 350 mg/m3 vapour

Ingredient comments The Workplace Exposure Limited quoted is an advisory level from the CEFIC-HSPA The

figures quoted below are taken from the registration document and/or the substance

manufacturers data sheet.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

**DNEL** Industry/Professional - Dermal; Long term systemic effects: 44 mg/kg/day

Industry/Professional - Inhalation; Long term systemic effects: 330 mg/m3/8h General population - Dermal; Long term systemic effects: 26 mg/kg/day General population - Inhalation; Long term systemic effects: mg/m3/24h

General population - Oral; Long term systemic effects: mg/kg/day

# 8.2. Exposure controls

#### Protective equipment









#### **BARTOLINE WHITE SPIRIT**

Appropriate engineering controls

This product is not to be used under conditions of poor ventilation. This product must not be handled in a confined space without adequate ventilation. Mechanical ventilation or local exhaust ventilation may be required. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid inhalation of vapours and spray/mists. Use explosion-proof electrical, ventilating and lighting equipment. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures.

Personal protection

Protective engineering solutions should be implemented and in use before Personal Protective Equipment (PPE) is considered.

Eye/face protection

Wear EN 166 approved chemical safety goggles where eye exposure is reasonably probable.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. It is recommended that gloves are made of the following material: Nitrile rubber. Polyvinyl chloride (PVC). Viton rubber (fluoro rubber). Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear an apron and protective sleevelets made of the following material: Nitrile rubber. Polyvinyl chloride (PVC). Viton rubber (fluoro rubber). Wear anti-static protective clothing if there is a risk of ignition from static electricity.

Hygiene measures

Persons with impaired lung function should not handle this product.. Pregnant or breastfeeding women should not work with this product if there is any risk of exposure. Wash hands thoroughly after handling. Wash promptly if skin becomes contaminated. Care should be taken to avoid contact with contaminants when removing contaminated clothing. Promptly remove any clothing that becomes wet or contaminated. Remove contaminated clothing and protective equipment before entering eating areas. Change work clothing daily before leaving workplace. Wash contaminated clothing before reuse. Wash at the end of each work shift and before eating, smoking and using the toilet. Use appropriate hand lotion to prevent defatting and cracking of skin. Do not eat, drink or smoke when using this product.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate BS EN 405:2001+A1:2009 certified respirators. In the case of vapour formation use a respirator with filter model:. Type A.

In case of vapours and aerosol formation:. Respirator with combination filter for vapour/particulate, Type A/P2.

Warning! filters have a limited use duration.

Thermal hazards

Not Applicable

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Store in a demarcated bunded area to prevent release to drains and/or watercourses. Keep container tightly sealed when not in use. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

# SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

# **BARTOLINE WHITE SPIRIT**

**Appearance** Colourless liquid.

Clear. Colour

Odour aromatic hydrocarbons

Odour threshold Not available. pН Not applicable. Melting point

Initial boiling point and range 158 - 191 degrees C 316 - 376 degrees F

Not applicable.

Flash point ~ 40°C ISO 13736 ~ 104°F ISO 13736

**Evaporation rate** ~ 57 EtEt=1 DIN 53170

**Evaporation factor** Not available. Flammability (solid, gas) Not applicable.

Upper/lower flammability or

explosive limits

Upper flammable/explosive limit: 7 % Lower flammable/explosive limit: 0.7 %

Other flammability Not applicable. Vapour pressure 1.9 hPa @ 20°C Vapour density Not available.

Relative density ~ 0.785 @ 15°C **Bulk density** Not applicable.

Solubility(ies) Substance is a UVCB. Standard tests for this endpoint are not appropriate.

Partition coefficient Not available. **Auto-ignition temperature** >230°C/>446°F **Decomposition Temperature** Not available.

Kinematic viscosity  $\leq 20.5 \text{ mm}^2\text{/s. } 0.95 \text{ mm}2\text{/s} \textcircled{@} 40^{\circ}\text{C}$ Viscosity

**Explosive properties** Not considered explosive based on chemical structure and oxygen balance considerations.

Explosive under the influence

of a flame

Not considered to be explosive.

Oxidising properties Does not meet the criteria for classification as oxidising.

Comments Information declared as "Not available" or "Not applicable" is not considered to be relevant to

the implementation of the proper control measures.

9.2. Other information

Volatile. Volatility

This product contains a maximum VOC content of 785 g/l. Volatile organic compound

# SECTION 10: Stability and reactivity

# 10.1. Reactivity

Reactivity The reactivity data for this product will be typical of those for the following class of materials:

Hydrocarbons. There are no known reactivity hazards associated with this product.

# 10.2. Chemical stability

# **BARTOLINE WHITE SPIRIT**

Stability Stable under the prescribed storage conditions. See Section 10.3 (Possibility of hazardous

reactions) for further information.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Under normal conditions of storage and use, no hazardous reactions will occur.

10.4. Conditions to avoid

Conditions to avoid Containers can burst violently or explode when heated, due to excessive pressure build-up.

Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Do not pressurise, cut, weld, drill, grind or otherwise expose containers to heat

or sources of ignition. Avoid the accumulation of vapours in low or confined areas.

10.5. Incompatible materials

Materials to avoid Avoid contact with the following materials: Strong acids. Oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon

monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

**Toxicological effects**The toxicity of this substance has been assessed during REACH registration. See information

on individual substances below.

Germ cell mutagenicity

**Genotoxicity - in vitro**Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Toxicological information on ingredients.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) 100 %

**Toxicological effects** The toxicity of this substance has been assessed during REACH registration.

Acute toxicity - oral

Acute toxicity oral (LD50

15,000.0

mg/kg)

**Species** Rat

**ATE oral (mg/kg)** 15,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> 3,400.0

mg/kg)

Species Rat

ATE dermal (mg/kg) 3,400.0

Skin corrosion/irritation

Animal data Conclusive data but not sufficient for classification. Not irritating.

Serious eye damage/irritation

# **BARTOLINE WHITE SPIRIT**

Serious eye This substance does not meet the EU criteria for classification. - Burning feeling

damage/irritation and temporary redness.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

**Skin sensitisation**Based on available data the classification criteria are not met.

Germ cell mutagenicity

**Genotoxicity - in vitro**Based on available data the classification criteria are not met.

Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity -

fertility

Based on available data the classification criteria are not met.

Reproductive toxicity -

development

This substance has no evidence of toxicity to reproduction.

Specific target organ toxicity - single exposure

**STOT - single exposure** Vapours may cause drowsiness and dizziness.

Target organs Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Target organs Central nervous system

Aspiration hazard

Aspiration hazard May be fatal if swallowed and enters airways. Entry into the lungs following

ingestion or vomiting may cause chemical pneumonitis.

**Inhalation** Vapours inhaled in strong concentrations have a narcotic effect on the central

nervous system. Irritation of the respiratory tract due to excessive fume. Causes headache, drowsiness or other effects to the central nervous system, loss of

consciousness.

**Ingestion** Symptoms: Nausea, vomiting, abdominal pain. Harmful: If swallowed accidentally,

the product may enter the lungs due to its low viscosity

and lead to the rapid development of very serious inhalation pulmonary lesions

(medical survey during 48 hours).

**Skin contact** Prolonged or repeated contact may dry skin and cause irritation. Frequent or

prolonged skin contact destroys the lipacid cutaneous layer and may cause

dermatitis.

Eye contact This mixture does not meet the EU criteria for classification. Any eye contact may

cause a burning feeling and temporary redness.

Route of entry Inhalation Ingestion Oral Skin and/or eye contact

Target organs Central nervous system Eyes Skin Respiratory system, lungs

# **BARTOLINE WHITE SPIRIT**

Medical symptoms Symptoms following overexposure to vapour may include the following: Central

nervous system depression. Confusion, agitation and/or excitation.

**Medical considerations** The following pre-existing or historic medical conditions of the worker may lead to

> an increased risk of adverse health effects following exposure to this product: Chronic respiratory and obstructive airway diseases. History of smoking. Pre-

existing eye problems. Skin disorders and allergies.

# SECTION 12: Ecological Information

# Ecological information on ingredients.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) 100 %

Toxic to aquatic life with long lasting effects. **Ecotoxicity** 

12.1. Toxicity

**Toxicity** See information on ingredient substances below.

Ecological information on ingredients.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) 100 %

Acute toxicity - fish LL<sub>50</sub>, 96 hours: 10-30 mg/l, Onchorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic

invertebrates

EC<sub>50</sub>, 48 hours: 10-22 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC<sub>50</sub>, 72 hours: 4.1 mg/l, Pseudokirchneriella subcapitata

life stage

Chronic toxicity - fish early NOEC, 28 days: 0.13 mg/l, Onchorhynchus mykiss (Rainbow trout)

Chronic toxicity - aquatic

invertebrates

NOEC, 21 days: 0.28 mg/l, Daphnia magna

# 12.2. Persistence and degradability

Ecological information on ingredients.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) 100 %

Persistence and degradability

Readily biodegradable (75 % after 28 days).

12.3. Bioaccumulative potential

Partition coefficient Not available.

Ecological information on ingredients.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) 100 %

Bioaccumulative potential Measured experimental data on hydrocarbon UVCB substances are not

meaningful, since each of the constituents is likely to behave differently.

12.4. Mobility in soil

Mobility Substance is a UVCB. Standard tests for this endpoint are not appropriate.

Ecological information on ingredients.

# **BARTOLINE WHITE SPIRIT**

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) 100 %

Mobility

Substance is a UVCB. Standard tests for this endpoint are not appropriate.

# 12.5. Results of PBT and vPvB assessment

Ecological information on ingredients.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) 100 %

**Results of PBT and vPvB** This substance is considered not to be PBT and vPvB.

assessment

#### 12.6. Other adverse effects

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### General information

The generation of waste should be minimised or avoided wherever possible. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. External recovery, treatment, recycling and disposal of waste should comply with all applicable local and/or national regulations. Waste material and any included combustible absorbent and containers should be suitable for incineration at an approved facility. This material and its container must be disposed of as hazardous waste. Waste packaging should be collected for reuse or recycling. The packaging must be empty (drop-free when inverted). When handling waste, the safety precautions applying to handling of the product should be considered.

#### Disposal methods

Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Waste material and any included combustible absorbent and containers should be suitable for incineration at an approved facility. This material and its container must be disposed of as hazardous waste.

# Waste class

When this product, in its liquid state, as supplied becomes waste it should be disposed of as hazardous waste using the waste code 08 01 11 waste paint and varnish containing organic solvents or other dangerous substances.

Empty used containers should be disposed of as waste code 15 01 10 packaging containing residues of or contaminated by dangerous substances.

When used the removed sludge should be disposed of using waste code 08 01 13 sludges from paint and varnish remover containing organic solvents or other dangerous substances. Any absorbents used for clearing up spills should be disposed of using waste code 15 02 02 absorbents contaminated by dangerous substances.

# SECTION 14: Transport information

General Limited quantity size 5 litres (LQ 7) Excepted Quantity size 30ml (E1)

14.1. UN number

UN No. (ADR/RID) 1300 UN No. (IMDG) 1300 UN No. (ICAO) 1300 1300 UN No. (ADN)

# 14.2. UN proper shipping name

# **BARTOLINE WHITE SPIRIT**

Proper shipping name

(ADR/RID)

TURPENTINE SUBSTITUTE

Proper shipping name

TURPENTINE SUBSTITUTE

(IMDG)

Proper shipping name (ICAO) TURPENTINE SUBSTITUTE

Proper shipping name (ADN) TURPENTINE SUBSTITUTE

# 14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

# Transport labels



# 14.4. Packing group

ADR/RID packing group III

IMDG packing group

ADN packing group

ICAO packing group

# 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



# 14.6. Special precautions for user

EmS F-E, S-E

ADR transport category 3

Emergency Action Code 3Y

Hazard Identification Number 30

(ADR/RID)

Tunnel restriction code (D/E)

# 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

# SECTION 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **BARTOLINE WHITE SPIRIT**

National regulations Control of Substances Hazardous to Health Regulations 2002 (as amended).

Dangerous Substances and Explosive Atmospheres Regulations 2002.

EH40/2005 Workplace exposure limits.

Health and Safety at Work etc. Act 1974 (as amended).

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment

Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009

No. 716).

Users of this product are reminded of their duties under the current Control of Substances Hazardous to Health Regulations and a suitable and sufficient assessment of all the risk should be undertaken before using this product. The guidelines given in the HSE publication COSHH ESSENTIALS - Easy Steps To Control Chemicals gives sound advice for deciding

safe working control measures.

**EU legislation** Commission Decision 2000/532/EC as amended by Decision 2001/118/EC establishing a list

of wastes and hazardous waste pursuant to Council Directive 75/442/EEC on waste and

Directive 91/689/EEC on hazardous waste with amendments.

Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at

work (as amended).

Dangerous Substances Directive 67/548/EEC.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Guidance CHIP for everyone HSG228.

Introduction to Local Exhaust Ventilation HS(G)37.

The spraying of flammable liquids HSG178.

Workplace Exposure Limits EH40.

Health and environmental

listings

Regulation (EC) 689/2008 of the European Parliament and of the Council of 17 June 2008

concerning the export and import of dangerous chemicals (as amended).

Authorisations (Title VII

Regulation 1907/2006)

Restrictions (Title VIII

Regulation 1907/2006)

No specific authorisations are known for this product.

No specific restrictions on use are known for this product.

#### 15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

# Inventories

#### **EU - EINECS/ELINCS**

All the ingredients are listed or exempt.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) 100 %

# Canada - DSL/NDSL

All the ingredients are listed or exempt.

# **US-TSCA**

All the ingredients are listed or exempt.

#### **BARTOLINE WHITE SPIRIT**

Australia - AICS

All the ingredients are listed or exempt.

Japan - MITI

All the ingredients are listed or exempt.

Korea - KECI

All the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

Philippines - PICCS

All the ingredients are listed or exempt.

New Zealand - NZIOC

All the ingredients are listed or exempt.

#### SECTION 16: Other information

#### General information

The European Inventory of Existing Commercial Substances (EINECS) descriptions and numbers have been used historically to identify chemical substances. EINECS descriptions exist for a number of hydrocarbon substances derived from petroleum refining and chemical conversion. In the past this substances was identified by CAS 64742-82-1 but this description was overly broad as solvents have narrower hydrocarbon ranges. different classifications and different processing. A more focused and narrow definition was therefore required. REACH requires a clear and logical substance description and substance identification is a key component in registration. In order to facilitate appropriate registration of hydrocarbon solvents the Hydrocarbon Solvents Producers Association (HSPA) has conducted an in-depth assessment of hydrocarbon solvents in order to better characterize its substances and adopt a consistent substance identification system. This means that although the product has not changed (just how is described) there may be some difference as to what is displayed on the product labels as they were compiled using the old system.

Training advice

The information on directions for use can be found on the product label. It is important to ensure that anyone using this product in the workplace has been adequately trained and in particular: The use of personal protective equipment, methods of cleaning up and disposal of waste. The basic first aid arrangements.

Revision comments

DUE TO CHANGE OF CLASSIFICATION DATABASE THE REVISION NUMBERING HAS BEEN RESET. You should therefore look at the revision date rather than the revision number to ensure you have the most up to date version. NOTE: Lines within the margin indicate significant changes from the previous revision.

**Issued by** HS&E Manager.

Revision date 09/03/2015

Revision 2

SDS number 4652

SDS status Approved.

# **BARTOLINE WHITE SPIRIT**

Risk phrases in full R10 Flammable.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through

inhalation.

R66 Repeated exposure may cause skin dryness or cracking.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R65 Harmful: may cause lung damage if swallowed. R67 Vapours may cause drowsiness and dizziness.

Hazard statements in full H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

The information contained in this data sheet is provided in accordance with the requirements of the Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP). The product should not be used for purposes other than those shown in Section 1.2. As the specific conditions of use are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet is based on the present knowledge and the current EU and UK Legislation. It provides guidance on health, safety and environmental aspects of the product and should not be taken as a product specification.